

TRIOFLEX 7 ZONEN OCTO

- Electrically adjustable head and foot regions
- Flat motor
- Film coated slatted frame in multi-layer birch, with 44 slats
- Mounted in flexible TRIO caps covering the side rails
- Individually adjustable level of firmness in the centre zone
- Shoulder comfort zone
- Load distributing centre belt



Version	Electrically adjustable head and foot regions
Material	Slatted frame in stipple film coated glued multi-layer birch, stipple film coated cross rail in solid beech
Zone	7
Number of slats	44 - film coated in silver and anthracite
Slats storage	Mounted in flexible TRIO caps covering the side rails
Slats width	25 mm
Slats strength (standard / oversize)	8 mm / 10 mm
Facilities	Shoulder comfort zone, 9 adjustable levels of firmness, load distributing centre belt

Maximum load capacity	130 kg
Handle height	70 mm
Height	100 mm
Motor	Flat motor incl. emergency lowering function, standby < 0,4 W
Deliverable sizes	80, 90, 100 x 190, 200 cm
Overlength	210, 220 cm
Overwidth	120, 140 cm
Special sizes	On request

*data based on slatted frames measuring 90x200cm / subject to technical changes

<https://www.hansa-holz-kontor.de/en/product/trioflex-7-zonen-octo/>

© 2025 Hansa-Holz-Kontor